



US 20210071413A1

(19) **United States**(12) **Patent Application Publication**
Worch(10) **Pub. No.: US 2021/0071413 A1**(43) **Pub. Date: Mar. 11, 2021**(54) **HEAT INSULATING ELEMENT, BUILDING CONSTRUCTION AND METHOD FOR AVOIDING MOISTURE DAMAGE AT A BUILDING**(71) Applicant: **SAINT-GOBAIN ISOVER,**
Courbevoie (FR)(72) Inventor: **Anatol Worch, Kamen (DE)**(21) Appl. No.: **17/053,637**(22) PCT Filed: **May 22, 2019**(86) PCT No.: **PCT/EP2019/063230**

§ 371 (c)(1),

(2) Date: **Nov. 6, 2020**(30) **Foreign Application Priority Data**

May 22, 2018 (DE) 10 2018 112 260.8

Publication Classification(51) **Int. Cl.**

<i>E04B 1/80</i>	(2006.01)
<i>E04B 1/76</i>	(2006.01)
<i>E04C 2/296</i>	(2006.01)
<i>E04D 11/02</i>	(2006.01)
<i>E04D 13/16</i>	(2006.01)
<i>B32B 5/02</i>	(2006.01)
<i>B32B 19/06</i>	(2006.01)
<i>B32B 21/02</i>	(2006.01)
<i>B32B 21/10</i>	(2006.01)

(52) **U.S. Cl.**

CPC *E04B 1/80* (2013.01); *B32B 2262/108* (2013.01); *E04B 1/7675* (2013.01); *E04C 2/296* (2013.01); *E04D 11/02* (2013.01); *E04D 13/1618* (2013.01); *B32B 5/02* (2013.01); *B32B 19/06* (2013.01); *B32B 21/02* (2013.01); *B32B 21/10* (2013.01); *B32B 2307/304* (2013.01); *B32B 2419/06* (2013.01); *B32B 2262/101* (2013.01); *B32B 2262/02* (2013.01); *E04B 1/7645* (2013.01)

(57) **ABSTRACT**

The invention relates to a heat insulating element (4) for an interior insulation, a facade insulation, a roof insulation, or the like at a building (1), comprising an insulating body (41) which is of diffusion-open design. The heat insulating element (4) is characterized in that it further comprises a fabric (42), especially a fleece, which is of capillary-active design, and that the fabric (42) is arranged on a surface of the insulating body (41). Furthermore, the invention relates to a building construction, to a method for avoiding moisture damage at a building (1), and to the use of a heat insulating element of this type. This achieves an improved heat insulating element (4) for avoiding moisture damage at a building (1) by means of which it is possible to accelerate drying of the region concerned in the case of the accumulation of water, especially condensation water, with simple means. Furthermore, an appropriate building construction is provided in which moisture damage can be avoided more reliably, and an improved method for avoiding moisture damage at a building (1) is provided.

